

PATENT ABSTRACTS OF JAPAN

(11)Publication number : 04-164685

(43)Date of publication of application : 10.06.1992

(51)Int.Cl.

B41M 5/26

(21)Application number : 02-293261

(71)Applicant : KANZAKI PAPER MFG CO LTD

(22)Date of filing : 29.10.1990


(72)Inventor : SHIMIZU YOSHIHIRO
YOSHIZAWA KATSUAKI
MIFUJI HISAYOSHI
YODA SHUJI

(54) THERMAL RECORDING MATERIAL

(57)Abstract:

PURPOSE: To obtain a thermal recording material improved in the preservability of a recording image, especially, in the plasticizer resistance and oil resistance thereof, generating no background fog and enhanced in recording density and recording sensitivity by adding at least one kind of a compound having an epoxy group and a specific compound.

CONSTITUTION: A thermal recording material utilizes the color reaction of a colorless or light-colored basic dye and a developer capable of forming a color upon the contact with said dye and contains at least one kind of a compound having an epoxy group and a compound represented by general formula (I). The compound having an epoxy group is selected from a novolac type epoxy resin, a bisphenol A type epoxy resin and a diphenylsulfonic acid derivative having an epoxy group. The compound represented by the general formula (I) is usually added to a thermal recording layer and, concretely, dibenzyl oxalate is pref. The use amount of the compound represented by the general formula (I) is about 10-1000 pts.wt., pref., 50-500 pts.wt. per 100 pts.wt. of the basic dye.



(I) (1)